

Standard Series TSP-72



Trunsun High Efficiency Polycrystalline Solar Module
325-345W



Approved Technology

Approved practice for different operating conditions



Positive Tolerance

Positive tolerance brings more power for free



Mechanical Load Endurance

Excellent mechanical load resistance: wind loads (2400Pa) & snow loads (5400Pa)




Guaranteed Reliability Against Harsh Environment

Due to Complicated Quality control system, offer survival solar module in harsh environment



LINEAR PERFORMANCE WARRANTY



12years Product Material & Workmanship

25years Linear Performance Warranty

About Trunsun Solar

Trunsun Solar, established in 2008, is dedicated to providing solar products with high quality, excellent performance and strong after-sales support. The company not only has strong financial support but also never stops innovating. Trunsun Solar will keep delivering the diversified solar products for all kinds of renewable energy generation systems around the world.

Standard Series TSP-72 Trunsun High Efficiency Polycrystalline Solar Module

ELECTRICAL DATA @ STC*		TSP325-72	TSP330-72	TSP335-72	TSP340-72	TSP345-72
Peak Power (Pmax)	(W)	325	330	335	340	345
Maximum Power Voltage (Vmp)	(V)	37.75	38.11	38.38	38.60	38.86
Maximum Power Current (Imp)	(A)	8.61	8.66	8.73	8.81	8.88
Open-circuit Voltage (Voc)	(V)	45.68	45.96	46.24	46.51	46.79
Short-circuit Current (Isc)	(A)	9.14	9.20	9.46	9.57	9.68
Module Efficiency	(%)	16.77	17.02	17.28	17.54	17.80
Operating Temperature		-40°C~+85°C				
Maximum System Voltage		1000V				
Maximum Series Fuse Rating		15A				
Application Class		Class A				
Power Tolerance		0~+3%				

*STC (Standard Test Condition): Irradiance 1000W/ m², Module Temperature 25°C, AM 1.5

ELECTRICAL DATA @ NMOT*		TSP325-72	TSP330-72	TSP335-72	TSP340-72	TSP345-72
Peak Power (Pmax)	(W)	241	244	248	252	256
MPP Voltage (Vmp)	(V)	34.85	35.18	35.43	35.63	35.87
MPP Current (Imp)	(A)	6.91	6.95	7.01	7.07	7.13
Open Circuit Voltage (Voc)	(V)	42.91	43.18	43.44	43.69	44.01
Short Circuit Current (Isc)	(A)	7.40	7.45	7.66	7.75	7.81

*Under Nominal Module Operating Temperature (NMOT), Irradiance of 800W/ m², Spectrum AM 1.5, Ambient Temperature 20°C, Wind Speed 1m/s

TEMPERATURE CHARACTERISTICS	
Temperature coefficient of Pmax	-0.41%/°C
Temperature coefficient of Voc	-0.33%/°C
Temperature coefficient of Isc	0.05%/°C
NMOT	43±3°C


MECHANICAL DATA	
Cell Type	Poly-Crystalline, 6" inch
Cell Arrangement	72pcs (6×12)
Dimension (L×W×H)	1956×991×35mm
Weight	21.5kg
Front Cover	3.2mm Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67, 3 Bypass Diodes
Cable Type	4mm ²
Length of Cable	1200mm
Connector	PV Connector

PACKING MANNER	
Packing Type	40HQ
Piece/Pallet	30
Pallet/Container	24
Piece/Container	720



*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Zhejiang Trunsun Solar Co., Ltd. Reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

*Power measurement tolerance: ±3%

Current-Voltage Curve under different irradiance



Current-Voltage Curve under different working temperatures



Version 2019.04 © Zhejiang Trunsun Solar Co., Ltd All Rights Reserved.